


KK 1000		ÜTB no: 1001	
Dimensions	Shape:	Round conical	
	Volume under lid:	1,00 L +/- 8 ml	
	Full Filled Volume:	1.09 L +/- 8 ml	
	Top dia (Ext) without lid:	120 mm +/- 2 mm	Height without lid: 121 mm +/- 2 mm
	Top dia (Ext) with lid:	120 mm +/- 2 mm	Height with lid: 122 mm +/- 2 mm
	Base diameter (Ext):	105 mm +/- 2 mm	
Lid system	Safety system:	Tamper evidence lock	
	Safety circle:	Yes	
	Tamper proof:	Differs with lid type	
	Lid Types:	Standard	
Handle	Handles:	Plastic standard	
Printing	Decoration options:	Offset pail print Offset lid print	
	Printing Area:	92 X 365 mm	
	Printing gap:	0 mm	
	Printing overlap:	3 mm	
Plastic Material	Material options:	PP Copolymer	
	Masterbatch options:	General Colours: White 101, Transparent, Naturel, Other colours can be asked	
	Approved:	All plastic polymers, masterbatches and atistatic agents are approved by Turkish Ministry of Agr. and Rural Affairs. 	
Sturdiness	Stacking (Full):	6kg (=the max weight that the pail which is at the base of stack can carry Stacking test made on 23° C for 2 months with standart PP raw material. Stackability may vary with diffrent factors. Data above are for indication. For that reasons, customers should make their own tests to determine stacking and transportation quantities. For transparent materials the durability is lower, customers must consider that before stacking transparent products.	
Weight	Pail weight (nude):	43 g +/- 2 g	
	Lid weight:	12 g +/- 1 g	
	Weight plastic handle:	2 g +/- 0.5 g	
Packing	Palette		Lid carton box: YES
	1300x1100x2100 mm:	4500 pieces (with lids)	Carton box size: 550 x 420 x 450 mm
	No of cartons on palette:	9 pieces	Lids in a carton box: 1500 pieces
	Pieces per carton:	500 pieces	Carton boxes in a palette: 24 pieces
Performance	Hot filling:	The standart material has a very good heat resistance and the pail is suitable for hot filling. But, plastic pail become flexible when hot filled on high temperatures and customers must carefully stack after hot filling. After cooling of the product and pail, the pail regains its original stacking strength.	
	Cold reactions:	The standard PP material for white/coloured products resists temperatures up to -20° C. Deep freezing under -20° C require a special PP .Standard transparent products may become fragile at temperatures below 0° C and special transparent resins are available on request for applications below freezing.	
	Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 10 months after the date of the delivery,under to suitable storage.	
	Quality info:	Deviations in the product specifications in this data sheet can be 1% or less (i.e. 10 items per 1,000) on a 12 months basis are considered acceptable and therefore cannot be considered as a defect.	
Other:	UN approval:	NO	
	Notes:		